

NANUKTM
PROFESSIONAL PROTECTIVE CASES

MEDIUM
SERIES **918**

SPECIFICATIONS

Interior dimensions	L14.9" x W9.8 x H8.6" L378mm x W249mm x H218mm
Exterior dimensions	L16.9" x W12.9" x H9.3" L429mm x W328mm x H236mm
Weight (empty)	6.4 lbs 2.9 kg
Lid depth	2.1" 53mm
Base depth	6.5" 165mm
Max buoyancy	40 lbs 18.1 kg
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	Yes
Watertight	Yes - IP67
Warranty	Conditional lifetime guarantee

MATERIALS

Case shell	NK-7 high impact polypropylene
Latches	Nylon 66
Handle	NK-7 high impact polypropylene TPE
Purge valve	Nylon 66 Gore® membrane Silicone washers
Pins/hardware	304 stainless steel
Gasket	EPDM



CERTIFICATIONS

	IPX7 INGRESS PROTECTION - WATERPROOF
	IP6X INGRESS PROTECTION - DUSTPROOF
	ATA SPECIFICATION 300 - CATEGORY 1 IMPACT
 48cm (19") min.	ASTM D-4169 DC-18 - DROP TEST
	ASTM D-4169 DC-18 - VIBRATION
	ASTM D-4169 DC-18 - RAINFALL
 1 meter (3.28 ft)	MIL-STD-810F - IMMERSION

STANDARD FEATURES

- 1 - Powerclaw latching system
- 2 - Waterproof IP67 rated
- 3 - Impact resistant NK-7 resin
- 4 - Padlockable
- 5 - Stackable
- 6 - Molded-in bezel system
- 7 - Soft grip handle stay
- 8 - Automatic pressure release valve
- 9 - Integrated lid stay
- 10 - 100% stainless steel hardware
- 11 - Lifetime guarantee



AVAILABLE COLORS



AVAILABLE OPTIONS



CUSTOM OPTIONS

